

Survey began June 24th 1911 Frank Baier Rodman Stadia measure

Mr A C Hall } Interested parties properly notified
Mrs Smith }
Mr Smith } Mr A C Hall appeared

Began at NE Corner Sec 35 T14SR31E and retraced the lines of the Section
I then crossed lines from opposite 1/4 corners and at their intersection set the centre of Sec 35-T14SR31E
For this corner marked a rock + CS set in mound of rocks From which
A Pine 30' dia marked BTX Bears S 80° E 96 links
Plat shows Land of Johnson and Bearing of lines Corners established marked with O

July 24 1911

Michael Spears

No 34 For A C Hall Sec 26 T14S R31E Will Mer

Survey began June 26 1911 Frank Baier Rodman Stadia measure

Mr Koger was notified and appeared

Began at SE Cor Sec 26 T14SR31E

Ran North to the E 1/4 cor Sec 26

Returned to a point half way and on line and set a Rock marked 1/2 CS for permanent 1/4 cor between SE cor and E 1/4 cor Sec 26 T14 R 31

Then retraced S Line of Sec 26 found S 1/4 cor missing no signs of blazed trees along whole line
Found the SW Cor Sec 26

Returned to a point 19,92 chs west of ^{and on line} SE cor Sec 26 and set a Rock ^{8x8x6} for permanent 1/4 cor marked 1/2 CS

From which a Pine 24' dia bears S 54° W 106 lks

A Pine 40' dia bears S 27° 30' E 16 lks

From this corner Ran S 40 ch falling E 64 links at a point halfway between E 1/4 cor and Centre of Sec 35
and at said point (ie halfway between E 1/4 cor and centre Sec 35) set a Rock marked 1/2 CS

From which A Pine 20' dia bears N 81° E 44 links

A Pine 12' dia bears S 7° E 40 links

Now after retracing the Section lines I returned to 1/4 cor between SE cor and E 1/4 cor Sec 26 and calculated

the means of courses and ran S 89° 04' W 19,93 Chais and set a Rock Quartz 6x4x8 marked 1/2 CS

From which A Pine 28' dia S 23° W 15 links. See plat opposite page Corner Established marked with O

Halls Ranch June 26 1911

Testimony of A. C. Hall concerning

the position of NW cor Sec 36 T14S

Range 31 E after being duly sworn

Mr Hall was asked by the Surveyor

to point out the original position of

this corner to the best of his ability

Mr Hall did so ^{in the presence of Michael Spears County Surveyor} to the best of his ability

Witness Frank Baier

Ad Aug 1 1911

Michael Spears

County Surveyor

The Surveyor then set a Rock block

12x8x6 marked with an S and 1 inch

East and CS on S side at the point

indicated by Mr Hall from the corner

the point mentioned in Ser field Notes

bears as follows N 6° W 30 ft 24'

N 86° W 35 ft - 32'