

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. Z-1

History of original corner establishment:

This corner was originally established by Bamford Robb in 1880 under GLO Contract Number 366. Surveyor General Field Notes state:

Set a basalt stone 14x12x6 in mound of stone for Standard cor. to secs. 36 & 31 Township 10 S, Ranges 34 & 35 E, from which

A Pine, 36 in. dia. bears N45°E, 47 lks. dist.  
A Pine, 30 in. dia. bears N20°W, 72 lks. dist.

In 1917, U.S. Forest Service Surveyor, Frank J. Van Winkle, visited this corner during his retracement of a portion of the Second Standard Parallel South. His record states:

A stone 13x10x6 ins. with 6 notches on two opposite edges and lying under the limb of a fallen tree. I reset cor. stone firmly in the ground which I find it, with notches on E & W edges; from cor,

Pine, 26 ins. dia., bears N18°W, 72 lks. dist., mkd. S36 T10 R34 BT  
Pine, 31 ins. dia., bears N35½°E, 47 lks. dist., mkd. S31 T10 R35 BT

Description of Corner Evidence Found:

Found a 12"x9"x8" stone in the center of a mound of stones with faint notches.

Ponderosa Pine stump, with scribing, bears N31°51'E, 31.8 ft. (Orig. Rec: N45°E, 31.02 ft.; Van Winkle Rec: N35½°E, 31.02 ft.)

Description of monument and accessories I established to perpetuate the original location of this corner:


Set 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown on the DIAGRAM, 27" in the ground and buried the original stone alongside the monument on the north side.

From Which:

- Ponderosa Pine, 30"dia., bears N50°30'W, 55.8 ft., scribed: T10S R34E S36 SC BT
- Ponderosa Pine, 12"dia., bears N10°45'W, 63.3 ft., scribed: T10S R34E S36 SC BT
- Ponderosa Pine, 10"dia., bears N20°15'E, 59.9 ft., scribed: T10S R35E S31 SC BT
- Ponderosa Pine, 12"dia., bears N42°45'E, 24.0 ft., scribed: T10S R35E S31 SC BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs and painted blaze red.

DIAGRAM



REGISTERED PROFESSIONAL LAND SURVEYOR

*Susan E. Newstetter*

OREGON JULY 26, 1989 SUSAN E. NEWSTETTER 2405

Exp. 12/31/94

This work was performed by: Susan E. Newstetter PLS 2405 Witnessed by: D. Mitchell Ferguson and Rick Saul November 5, 1992 Refer to Grant Co. Survey No. 1239

Office of Surveyor County of Grant  
State of OR I hereby certify that the within instrument was filed in this office for record on the 20<sup>th</sup> day of Jan., 1993  
Robert D. Bunch by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)