


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. C-22

History of original corner establishment:

None. Corner established this survey.



Description of Corner Evidence Found:

None. Corner established this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in the DIAGRAM, 12" in the ground and raised a mound of stone around the monument.

From Which:

Ponderosa Pine, 28" dia., bears N16°30'E, 17.1 ft., scribed: C-W 1/16 S1 BT
Lodgepole Pine, 12" dia., bears S51°45'W, 28.0 ft., scribed: C-W 1/16 S1 BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) and Property Boundary (54-2) signs 5' south and west of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Susan E. Newstetter

OREGON
JULY 26, 1989
SUSAN E. NEWSTETTER
2405

Renewal Date: 12/31/94

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: Rick Saul, Brad
Cates and D. Mitchell Ferguson
July 29, 1993
Refer to Grant Co. Survey No.: 1279

Office of Surveyor County of Grant
State of OR I hereby certify that the within instrument was
filed in this office for record on the 21 day of Jan, 1994
Robert D. Bazzell by _____
(COUNTY OFFICIAL) (DEPUTY)