

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. G-19

History of original corner establishment:

None. Corner established this survey.

DIAGRAM
T14S R27E
C1/4
•
S11
1993
PLS 2405

Description of Corner Evidence Found:

None. Corner established this survey.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2-1/2"x30" aluminum pipe with 3-1/4" aluminum cap, stamped as shown in the DIAGRAM, 26" in the ground.

From Which:

- White Fir, 18" dia., bears N69°15'E, 43.2 ft., scribed: C1/4 S11 BT
- White Fir, 10" dia., bears S85°30'E, 21.6 ft., scribed: C1/4 S11 BT
- Ponderosa Pine, 6" dia., bears S28°15'W, 14.5 ft., scribed: C1/4 S11 BT
- 5/8"x30" rebar, set 28" in the ground, with a yellow plastic cap marked PLS 2405, bears N47°15'W, 10.6 ft.

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' south of the monument. Nailed a brass washer stamped PLS 2405 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Susan E. Newstetter

OREGON
JULY 28, 1980
SUSAN E. NEWSTETTER
2405

Renewal Date: 12/31/94

This work was performed by:
Susan E. Newstetter PLS 2405
Witnessed by: Rick Saul, Brad
Cates and D. Mitchell Ferguson
July 29, 1993
Refer to Grant Co. Survey No.: 1279

Office of Surveyor County of Grant
State of OR hereby certify that the within instrument was
filed in this office for record on the 21 day of Jan, 1994
Robert L. Beaman by _____
(COUNTY OFFICIAL) (DEPUTY)