

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner was established by Homer D. Angell, US Deputy Surveyor, during the original survey Contract No. 725 dated March, 1901.

Set a shale stone 14x14x5 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on W face and raise a mound of stone 2 1/2 ft. base 1 1/2 ft. high W of cor., pits impractical.

DIAGRAM

T14S
R34E R35E

1/4
S24 | S19

1991
PLS 699

Description of corner evidence found:

Found a stone firmly set in the ground surrounded by stone, but did not find any markings.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 2"x30" aluminum pipe with a 2 1/2" aluminum cap, marked as shown in the diagram, 26" in the ground, replacing the rock which is turned upside down and buried on the north side of the monument. Improved the existing mound with rock & earth to be 30" in diameter by 4" high around the monument, from which new BTs and Accessories are:

- 13" Western larch bears S68°E, 50.8 feet scribed 1/4 S19 BT
- 12" White fir bears N16°W, 14.3 feet scribed 1/4 S24 BT
- An Orange DEEP bears N68°W, 2.2 feet buried 8" in the ground
- A Pink DEEP bears S16°E, 1.6 feet buried 8" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped aluminum washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 3.8 feet N and 28.5 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 23, 1991, I monumented the corner as herein described.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Leland L. Myers

OREGON
JULY 9, 1965
LELAND LEE MYERS
699

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF Nov., 1992

Robert D. Boyer

Grant County Surveyor

MAP OF SURVEY No. 1197