

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

Corner was established by George R. Campbell, US Deputy Surveyor, during the original survey Contract No. 724 dated September, 1900.

A black pine, 9 ins. diam. for 1/4 sec. cor., I mark 1/4 S19 on W. side, 20 on E. side; from which

A black pine 9 ins diam bears S86°E, (112.9')19½ lks dist marked 1/4 S BT

A tamarack 12 ins diam bears S26°W, (11.6')17½ lks dist marked 1/4 S BT

DIAGRAM

T14S R35E

1/4

S19 | S20

1991

PLS 699

**Description of corner evidence found:**

Found a dead and down corner tree with visible scribing.

9" black pine (1900 BT) and 12" tamarack (1900 BT) not found.

**Description of monument and accessories I established to perpetuate the original location of this corner:**

Set a 2"x30" aluminum pipe with a 2½" aluminum cap, marked as shown in the diagram, 26" in the ground, at the point where the corner tree had stood. Built a mound of rock & earth to be 30" in diameter by 4" high around the monument, from which new BTs and Accessories are:

7" White fir bears N43°W, 11.4 feet scribed 1/4 S20 BT

7" White fir bears N59°15'E, 3.9 feet scribed 1/4 S19 BT

A Blue DEEP bears S59°15'W, 2.0 feet and buried 6" in the ground

A Pink DEEP bears S43°E, 2.7 feet and buried 8" in the ground

Attached BT and an Attention signs to and painted a red band around each BT. Bearings were turned from the control traverse with a theodolite, basis of bearing being a solar observation that was made on the adjacent McCoy Cadastral Survey contract in 1987, to stamped aluminum washers nailed on new BTs in the scribed red-painted blazes or to the red-painted blazes or scars on old BTs. Distances were measured from a 60d spike, with an aluminum washer stamped PLS 699, which was driven into the side of each BT approximately one foot above the ground.

Set steel fence posts 4.3 feet N and 5.4 feet S of the corner on the National Forest boundary lines. Attached Forest Boundary signs to each post and an Attention sign to the N post.

I, Leland L. Myers, 587 E. Auburn St., P.O. Box 98, Sumpter, OR 97877, do hereby certify that on October 25, 1991, I monumented the corner as herein described.

FILED

IN THE OFFICE OF THE Grant COUNTY SURVEYOR

THIS 30 DAY OF Nov, 1992

Robert D. Baynes  
Grant County Surveyor

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Leland L. Myers*  
OREGON  
JULY 9, 1965  
LELAND LEE MYERS  
699

MAP OF SURVEY No. 1197