


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:
Corner not previously established.



G-19
F.B. 7 P. 63, 64

Description of corner evidence found:

None. Corner not previously established.

Description of monument and accessories established to perpetuate the original location of this corner:

At position as determined by survey set a 2-1/2"O.D.x30" long aluminum pipe 27" in ground with a 2-1/2" diameter aluminum cap marked as shown: No stone available for mound.

Marked bearing trees:

A 15" Ponderosa Pine bears South 35-3/4 East, 157.6 ft., scribed "C1/4S11BT"; a 14" Juniper bears South 65° West, 57.8 ft., scribed "C1/4S11BT". Painted a 6" red band and face blazes red. Nailed signs 54-9 and 54-3 to BT'S. Nailed a brass washer stamped "LS 1026" to face blazes of BT'S. Set a steel fence post 5 ft. North of cap with sign 54-9. Bearings are by staff compass and declination is 19-1/2° East.

I hereby certify that the above corner monument was established as herein described on October 19, 1989.

Witnesses: Wes G. Heigh
Paul D. Woodworth

See C.S. #1124

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David B. Armstrong

12/22/89 OREGON,
AUGUST 22, 1975
DAVID B. ARMSTRONG
1026

Office of.....*Surveyor*..... County of.....*Grant*.....
State of.....*Oregon*....., I hereby certify that the within instrument was filed in this office
for record on the.....*13*..... day of.....*Feb*....., 19.....*90*.....
Robert D. Baggett by.....
(COUNTY OFFICIAL) (DEPUTY)