


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 488 dated August 11, 1883.

Page 80 of the government field notes state:

- 4000 Set a post 3-1/2 ft long 3 ins square with marked stone 12 ins in ground for 1/4 sec cor marked 1/4 S on W face from which
 - A pine 36 ins dia bears S40°E 26 lks dist marked 1/4S BT.
 - A pine 40 ins dia bears S30°W 32 lks dist marked 1/4S BT



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

I found no evidence of marked stone.
Found rotted wood post remnants from which:

- A 29" DBH PP snag 12 ft. tall bears S30°W 32 lks. scribed 1/4S BT.
- A 24" Dia PP windfall bears S40°E 26 lks. scribed BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. iron pipe with brass cap marked:

23" in ground & raised a mound of stones around it to the top of the cap.
from which I scribe NEW BEARING TREES:

- A 17" DBH PP bears S89-1/2°W 36.3 Ft., scribed 1/4 S17 BT.
- A 13" DBH PP bears S14°E 46.7 Ft., scribed 1/4 S16 BT.

T16S
R33E
1/4
S17 | S16
1979
OPLS 1805

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 2 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
This corner was set August 22, 1979.
Witness: F.R. Palmer & L.R. Nevill

Office of County Surveyor County of Grant
State of Oregon , I hereby certify that the within instrument was filed
in this office for record on the day of , 19
 by
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
PROFESSIONAL
LAND SURVEYOR
OREGON
JULY 13, 1979
F. E. CALKINS
1805