CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Original corner set by Henry W. Cooke under contract number 488 dated August 11, 1883.

Page 105 of the government field notes state:

4003 Set a post 3-1/2 ft long 3 ins square with marked stone 24 ins in ground for 1/4 sec cor marked 1/4 S on N face from which
A pine 40 ins dia bears S34°E 44 lks dist marked 1/4S BT
A pine 36 ins dia bears N10°W 48 lks dist marked 1/4S BT

DIAGRAM



No record of subsequent remonumentation found in county records.

Description of corner evidence found:

I did not find the original corner post or marked stone. I re-establish the corner point from the 2 original BT stumps.
Measuring distances from the face of the scribing.
From the corner point:
A 31" Dia. 14" high PP stump bears S34°E 44 lks. scribed B.
A 28" Dia. 12" high PP stump bears N0°E 48 lks. scribed BT.

Description of monument and accessories I established to perpetuate the original location of this corner:

Set a 30" long 2-1/2" dia. iron pipe with brass cap marked:
19" in ground & raised a mound of stones around it.
from which I scribe NEW BEARING TREES:

A 7" DBH PP bears S23°E 25.6 Ft., scribed 1/4 S20 BT.
A 8" DBH PP bears N67°E 20.4 Ft., scribed 1/4 S17 BT.

T16S
R33E
S17
1/4
S20
1979
OPLS 1805

REGISTERED PROFESSIONAL LAND SURVEYOR
F. E. Calkins
OREGON
JULY 13, 1979
F. E. CALKINS
1805

Painted faces & bands around BT's red & attached BT & Attention tags.
Drove a 6 Ft. long steel fence post 1 3/4 Ft. in ground 6 Ft. N of corner & attached an attention tag to it.
Used steel tape & magnetic staff compass with 20° East variation, measuring to the center of the new BT's.
This corner was set August 27, 1979.
Witness: F.R. Palmer, S. Anderson & L.R. Nevill

Office of County Surveyor County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 4 day of Feb, 19 80

Robert D Bagott by _____
(COUNTY OFFICIAL) (DEPUTY)

FORM R6-7100-57 (9/71)

N-7