


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

G-5

History of original corner establishment:

STONE 15x15x5 IN MOUND

AARON F. YORK, CONTRACT #309, Nov. 18, 1878



Description of corner evidence found:

Found no original evidence.

Description of monument and accessories I established to perpetuate the original location of this corner

Set 32" X 2" flanged iron pipe with brass cap marked:

Ponderosa Pine, 21" Dia., BRS. S41 $\frac{1}{4}$ <sup>0</sup>E, 20.8 Ft. Distance.

Marked:  $\frac{1}{4}$  S8 BT

Douglas Fir, 11" Dia., BRS. N40 $\frac{1}{4}$ <sup>0</sup>W, 33.6 Ft. Distance.

Marked:  $\frac{1}{4}$  S7 BT

6' Iron Fence Post with "Survey Monument" sign within 5' of Corner.

All BTs have BT tag, painted red stripe and brass washer stamped: PLS 346; nailed to lower blaze.

T7S R26E  
 $\frac{1}{4}$   
S7 S8  
1979  
PLS 346

Office of County Surveyor County of Grant  
State of Oregon, I hereby certify that the within instrument was filed in this office  
for record on the 9 day of Oct 1979  
Robert D. Baggett by \_\_\_\_\_  
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Wayne O. Harris*  
OREGON  
MAY 6, 1955  
WAYNE O. HARRIS  
346