

The East quarter corner was set via proportionate measurement as, after extensive search no original evidence was recovered. I set a 2" x 30" flanged galvanized iron pipe with a 2-1/2" brass cap exposed 10" in a mound of stone, and mark the following trees, taking measurements to the center of tree at the lower blaze in which I place a brass washer marked L.S. 1679:

W. Fir 8" dia. bears N20°29'W 30.7 feet.  
D. Fir 11" dia. bears N38°01'E 11.6 feet.  
An unofficial B.L.M. pipe and brass cap bears S54°41'E 19.5 feet.

All of the remaining controlling corners were established by private land surveyors.

The section subdivision was computed as shown on the accompanying map. The boundary lines of the National Forest were posted with six foot steel fence post and attached Forest Boundary signs.

The following corner monuments and accessories were recorded at the corners shown on the accompanying map:

Section Corner  $\frac{24}{25} | \frac{19}{30}$  : Found a standard B.L.M. pipe and brass cap dated 1968, exposed 12" in a mound of stone (this monument is not of public record) from which:

P. Pine 20" dia. bears N38°01'E 16.9 feet  
(record N38-1/2°E 15.8 feet). N42°E 15.8 Original.  
Fir 42" dia. bears S6°27'E 20.8 feet  
(record S6-1/2°E 19.1 feet). S12°E 19.1 Original.  
Fir 18" dia. bears S56°W 38.0 feet  
(record S56°W 38.3 feet). Unofficial.  
P. Pine 36" dia. bears N38°10'W 37.7 feet  
(record N38°W 36.3 feet). N36°W 36.3 Original.

1/4 Corner  $\frac{24}{25}$  : Found a 2" G.I. pipe with a 2-1/2" brass cap exposed 12" in a mound of stone, from which:

P. Pine snag 36" dia. bears N12°07'E 40.7 feet  
(record N10°E 39.6 feet).  
P. Pine 14" dia. bears S51°18'W 30.7 feet  
(record S44°W 30.5 feet).

I mark a new tree as required, taking my measurements to the center of the tree at the lower blaze in which I place a brass washer marked L.S. 1679:

P. Pine 10" dia. bears N15°29'W 30.1 feet.

1/4 Corner  $\frac{23}{24}$  : Found a 2" G.I. pipe with a 2-1/2" brass cap exposed 24", from which:

P. Pine 18" dia. bears N72°22'E 28.2 feet  
(record N75°E 27.9 feet).  
P. Pine 8" dia. bears N63°12'W 44.7 feet  
(record N62°W 44.1 feet).

N 1/16 Corner  $\frac{23}{24}$  : Found a 2" G.I. pipe with a 2-1/2" brass cap exposed 30" in a mound of stone, from which:

P. Pine 15" dia. bears N16°39'W 160.6 feet  
(record N14°W 160.6 feet).  
P. Pine 16" dia. bears S63°08'E 70.9 feet  
(record S62-1/2°E 70.9 feet).

Section Corner  $\frac{14}{23} | \frac{13}{24}$  : Found a 2" G.I. pipe with a 2-1/2" brass cap exposed 6" from which:

Fir 12" dia. bears N34°19'E 23.9 feet  
(record N36°E 23.7 feet).