

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Index: V-15

Quarter corner Sec. 27 and 34, T.7S., R.31E., W.M.

Original corner was set by Frank Campbell under Contract Number 380 in 1881.

His record reads:

Set a basalt stone 15x15x8 and dug pit for 1/4 sec. cor. from which:

A pine 30 in. dia. bears N32°W, 39 lks.

A pine 24" in. dia. bears S28°W, 41 lks.

In 1974 PLS 848 remonumented this corner. His record

reads: Found 15"x15"x8" basalt stone with 1/4 marked

on face surrounded by a small mound of stone from

which: A down and dead pine log 40 ins. dia. with scribing visible bears

approximately N32°W, 26 ft. A rotten pine snag, 24 ins. dia. with

scribing visible bears S28°W 27.1 ft. Accepted stone as being in the

original position. Set 30"x2 1/2" iron pipe with 3" brass cap marked as

shown (see diagram) 20 ins. in the ground and placed the original stone

west and alongside pipe and surrounded the pipe with stones, from which

new BT's A fir 8 ins. dia. bears N56°W 14.2 ft. dist. marked T7SR31E1/4S27BT.

A fir 14 ins. dia. bears S50°W 19.1 ft. dist. marked T7SR31E1/4S34BT.

Description of corner evidence found:

Found the iron pipe with brass cap stamped as shown in the diagram.

From which:

A 15" dbh dead Douglas Fir 15' high bears S50°W, 19.1' with healed blaze.

A 24" dbh 7' high Ponderosa Pine snag bears S28°W, 27.1' with visible

scribe. A 11" dbh 10' high Douglas Fir snag bears N 56°W, 14.2' with

visible scribe. Dead and down pine BT N32°W, 26' not found.

Description of monument and accessories I established to perpetuate the original location of this corner:

The bearings were based on the record bearings of the existing witness trees.

I set the following new witness trees:

A 13" dbh Ponderosa Pine bears S11 3/4°W, 100.8' scribed 1/4S34BT.

A 13" dbh Douglas Fir bears N19 1/2°W, 42.6' scribed 1/4S27BT.

A 19" dbh Douglas Fir bears S59 1/4°E, 67.3' scribed 1/4S34BT.

A 14" dbh Western Larch bears N73 3/4°E, 101.6' scribed 1/4S27BT.

An aluminum washer stamped RLS852 is nailed between the letters B and T on each new tree. All the BT's have LSM and BT signs attached.

Painted 6" red bands around all the trees and painted the scribe blazes red.

This work was completed December 28, 1993.



David L. Haddock
 OREGON
 JULY 12, 1968
 DAVID L. HADDOCK
 852

Office of Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed
 in this office for record on the 14 day of Feb, 1994.

Robert D. Baggett
 (COUNTY OFFICIAL)

by _____
 (DEPUTY)