


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established in 1881 by F. W. Campbell under General Land Office Contract No. 380.



Surveyor General Records (Notes) states:

- Set a pine post for Cor. to Secs. 5, 6, 31 & 32 from which
- A fir 40 in. dia. bears N 20°E 67 lks.
- A fir 20 in. diam. bears S36°E 134 lks.
- A fir 30 in. dia. bears N52°W 170 lks.
- No other tree convenient.

(No subsequent remonumentations in county records)

Description of corner evidence found:

Found two original BT's:

- A fir 40 in. Dia. dead and down
- A fir 20 in. dia., a stump

Description of monument and accessories established to perpetuate the original location of this corner


Set a 30 in. x 2½ in. iron pipe with 3 in. brass cap, marked as shown at record bearing and distance for the corner to Sections 31, 32, 5 & 6, from two original located BT's from which new BT's:

- A fir 14 in. dia. bears N15°E 16.9 ft. marked T7S, R31E S32 BT
- A fir 10 in. dia. bears S25°E 15.6 ft. marked T8S R31E S5 BT
- A pine 10 in. dia bears S41°W 22.3 ft. marked T8S R31E S6 BT.
- A fir 10 in. diam. bears N11°W 19.9 ft. marked T7S R31E S31 BT.

Distance to brass washer in the blaze of each tree. Set a steel fence post approximately 5 ft. East from corner with Forest Boundary sign attached.

Used steel tape and magnetic compass with declination = 20°E.

REGISTERED PROFESSIONAL LAND SURVEYOR
Douglas M. Ferguson
OREGON
 JULY 12, 1968
DOUGLAS M. FERGUSON
 848



Office of.....County Surveyor..... County of Grant.....
 State of Oregon....., I hereby certify that the within instrument was filed in this office for record on the 16 day of Nov. 1972, at 1 o'clock p.m., (signed)
Douglas M. Ferguson by _____
 (COUNTY OFFICIAL) (DEPUTY)