


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally set by F.W. Campbell under Contract No. 380 dated March 19, 1881. The notes state that a marked basalt stone 10x6x6 was set & pits were dug from which:
A 24" Pine bears S11°E 40 lks (26.4 feet) marked $\frac{1}{4}$ SBT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

Found a marked basalt stone 10 $\frac{1}{2}$ x8 $\frac{1}{2}$ x6 $\frac{1}{2}$ " from which:
A rotten pine stump bears S6 $\frac{1}{2}$ °E 26.4 feet

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 24 inches in the ground and surrounded with a mound of stones to the cap. Placed original stone in mound.

Set a steel fence post East of the corner and attached sign 54-4.

Established 2 new BT's:

A 12" Pine bears N79 $\frac{1}{2}$ °W 8.0 feet scribed $\frac{1}{4}$ S 24 BT

A 12" Pine bears S86°E 19.3 feet scribed $\frac{1}{4}$ S 25 BT

New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 to all BT's and painted a red ring around the trees above the upper blaze

Used steel tape and magnetic compass with 19 $\frac{1}{2}$ ° east declination. Measured to center of Bts.

See map of survey


This corner set October 25, 1979

Witnesses: D. Kaufman, PLS
D. Bartleson
C. Kelly

REGISTERED
PROFESSIONAL
LAND SURVEYOR

William R. Wells

OREGON
JULY 22, 1977
WILLIAM R. WELLS
1106



Office of _____ County Surveyor _____ County of Grant
State of Oregon, I hereby certify that the within instrument was filed in this office
for record on the 9 day of Jan 1980
Robert D. Baggett by _____ (DEPUTY)
(COUNTY OFFICIAL)