

SURVEY NO. 67A

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250

Surveyed for: U. S. Forest Service  
Umatilla National Forest  
2517 S. W. Hailey Avenue  
Pendleton, Oregon 97801

Location: Located in Sections 1 and 2, Township 8 South, Range 32 East, Willamette Meridian, Grant County, Oregon.

Purpose: To monument the corners and mark the property boundary of the National Forest lands as shown on the accompanying map.

Procedure: All controlling corners were encompassed in a series of closed traverses made with a Wild T-2 theodolite and an H-P 3805A E.D.M.

An extensive search was made in the vicinity of the one quarter corner of 3 and 2, as well as the one quarter corner of 1 and 12 prior to acceptance of the proportion positions. I also made a search for original evidence at the monumented position of the section corner of sections 1, 2, 35 and 36. This corner is a B.L.M. proportion corner.

RECEIVED AND  
FILED

MAY 27 1981

OFFICE OF COUNTY SURVEYOR

*Robert O. Sargent*  
Attest: *James E. Williams*

All of the B.L.M. monuments found, with exception of the East 1/16 corner common to sections 1 and 36 are dated 1968 and there exists no public record of their origin or method of establishment. The East 1/16 corner common to sections 1 and 36 is dated 1980 and is likewise not of record. This corner proved to be within acceptable limits and was used in the subdivision of section 1.

The following corner monuments and accessories were recorded at the corners:

Section corner  $\frac{116}{1217}$ : Found a standard B.L.M. pipe and brass cap dated 1968 and exposed 5 inches (This monument is not of public record) from which:

- D. Fir 14" dia. bears N77°01'E 36.1 feet  
(B.L.M. N 77-1/2°E 36.6 feet)
- W. Fir 16" dia. bears S62°40'E 23.7 feet  
(B.L.M. S79-1/2°E 23.8 feet)
- Tamarack snag 11" dia. bears S37°45'E 11.5 feet  
(B.L.M. S32°E 13.2 feet)
- W. Fir 18" dia. bears S20°50'W 17.2 feet  
(B.L.M. S23°W 17.1 feet)
- Tamarack snag 9" dia. bears S70°04'W 20.2 feet  
(B.L.M. S70°W 19.8 feet)
- Fir stump 18" dia. bears N68°29' W 8.5 feet  
(B.L.M. N75°W 8.0 feet)
- Tamarack 22" dia. bears N56°38'W 48.3 feet  
(B.L.M. N56-1/2°W 48.2 feet)

1/4 corner  $\frac{116}{1217}$ : Found a standard B.L.M. pipe and brass cap dated 1968, exposed 9" in a mound of stone. (This monument is not of public record.) from which:

- P. Pine snag 7" dia. bears N50°17'E 34.3 feet  
(B.L.M. N51°E 34.3 feet)
- P. Pine 10" dia. bears S45°E 4.3 feet  
(record S45°E 4.0 feet)
- P. Pine 17" dia. bears N68°03'W 9.3 feet  
(record N65°W 9.2 feet)