

N 1/16 corner $\begin{matrix} 2 \\ | \\ 1 \end{matrix}$: Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 4" in a mound of stone, from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- P. Pine 13" dia. bears N81°47'E 28.1 feet
- P. Pine 16" dia. bears N59°19'W 77.8 feet

1/4 corner $\begin{matrix} 2 \\ | \\ 1 \end{matrix}$: Found a standard B.L.M. pipe and brass cap dated 1968, exposed 4" in a mound of stone (This monument is not of record) from which:

- Tamarack 24" dia. bears N86°56'E 26.7 feet
(record N87°E 27.1 feet)
- W. Fir snag 12" dia. bears S72°28'E 21.6 feet
(B.L.M. S69-1/2°E 21.5 feet)
- D. Fir 16" dia. bears S32°02'W 48.7 feet
(B.L.M. S33°W 48.5 feet)

S 1/16 $\begin{matrix} 2 \\ | \\ 1 \end{matrix}$: Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 6" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 9" dia. bears S59°53'E 28.3 feet
- W. Fir 10" dia. bears S68°18'W 41.5 feet

Section corner $\begin{matrix} 2 \\ | \\ 1 \\ | \\ 1 \\ | \\ 2 \end{matrix}$: Found a standard B.L.M. pipe and brass cap dated 1967, exposed 20" in a mound of stone (This monument is not of record) from which:

- Fir 14" dia. bears N66°25'E 25.5 feet
(B.L.M. N68°E 25.4 feet)
- Fir 12" dia. bears S82°53'E 42.6 feet
(B.L.M. S81°E 42.6 feet)
- Fir 16" dia. bears S6°27'W 48.8 feet
(B.L.M. S7-1/2°W 48.8 feet)
- Fir 18" dia. bears N30°02'W 45.5 feet
(record N27°W 45.5 feet B.L.M. N38°W 71.3 feet)

W 1/16 corner $\begin{matrix} 1 \\ | \\ 2 \end{matrix}$: Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 8", from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 11" dia. bears N73°38'E 34.0 feet
- D. Fir 8" dia. bears S16°44'E 12.0 feet

1/4 corner $\begin{matrix} 1 \\ | \\ 2 \end{matrix}$: Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 6" in a mound of stone, from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 10" dia. bears N37°53'W 51.4 feet
- P. Pine 10" dia. bears S27°39'W 37.2 feet

E 1/16 corner $\begin{matrix} 1 \\ | \\ 2 \end{matrix}$: Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 8" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 14" dia. bears S34°54'W 42.7 feet
- W. Fir 9" dia. bears N58°21'W 26.9 feet