

NE 1/16 corner Section 1 : Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 8" in a mound of stone from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 18" dia. bears S30°46'E 20.7 feet
- D. Fir 15" dia. bears S77°13'W 46.6 feet

CE 1/16 corner Section 1 : Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 15" in a mound of stone from which I marked the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 13" dia. bears N84°32'W 11.8 feet
- D. Fir 18" dia. bears N8°02'W 7.0 feet

C 1/4 corner Section 1 : Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 5" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 6" dia. bears S69°21'E 40.0 feet
- W. Fir 6" dia. bears S26°17'W 17.0 feet

CN 1/16 corner Section 1 : Set a 2" x 30" flange G.I. pipe with a 2-1/2" brass cap exposed 5" in a mound of stone from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- P. Pine 11" dia. bears S5°04'W 28.1 feet
- D. Fir 15" dia. bears N79°45'W 68.3 feet

SW 1/16 corner Section 1 : Set a 2" x 30" flanged G.I. pipe with a 2-1/2" brass cap exposed 3" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 10" dia. bears S86°38'E 16.8 feet
- D. Fir 9" dia. bears N25°05'W 11.5 feet

1/4 corner 35₂ : Found a standard B.L.M. pipe and brass cap dated 1967 and exposed 4" (This monument is not of record.) from which:

- P. Pine 11" dia. bears N5°15'E 98.5 feet
(B.L.M. N4-1/2°E 98.7 feet)
- Pine stub bears N61°35'E 26.5 feet
(record N78°E 25.7 feet B.L.M. N62°E 25.7 feet)
- Pine stump 30" dia. bears S23°07'E 93.3 feet
(record S19°E 87.8 feet)
- P. Pine 12" dia. bears S8°46'E 134.1 feet
(B.L.M. S9-1/2°E 131.7 feet)

Section corner 34₃₅₃₁₂ : Found a standard B.L.M. pipe and brass cap dated 1967 and exposed 12" in a mound of stone (This monument is not of record.) from which:

- Pine stump 27" dia. bears N47°26'E 32.5 feet
(record N48°E 31.0 feet)
- Rock 4' x 4' x 3' marked B.O. bears N62°08'E 31.0 feet
(B.L.M. N62-1/2°E 31.0 feet)