

SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250

Survey For: The U. S. Forest Service
Umatilla National Forest
2517 S. W. Hailey Avenue
Pendleton, OR 97801

Location: Located in Sections 3 and 4, Township 8 South, Range 32
East of the Willamette Meridian, Grant County, Oregon.

Purpose: To monument and mark the property boundary of the National
Forest lands located in said Sections 3 and 4.

Procedure: All controlling corners were tied via a series of closed
traverses using a Wild T-2 theodolite and an H-P 3805A
E.D.M.. The double proportion position for the Section
corner common to Sections 3, 4, 9 and 10 was determined
from previous control acquired during the performance of
this contract. This information is illustrated on a separate
Map of Survey.

The North quarter corner of Section 3 is a B.L.M. proportion
corner which I utilized for the subdivision of said Section
3. The other found B.L.M. monuments found were set circa
1968 from original evidence, however, these monuments are
not of public record.

The following monuments and accessories were recorded at
the corners:

Section corner $\frac{34}{31} \frac{35}{2}$: Found a standard BLM pipe and brass
cap dated 1967 and exposed 12" in a mound of stone (this
monument is not of record) from which:

Pine stump 27" dia. bears N47°26'E 32.5 feet
(record N48°E 31.0 feet)
Rock 4' x 4' x 3' marked B.O. bears N62°08'E 31.0 feet
(BLM N62-1/2°E 31.0 feet)
Rock 2' x 2' x 1/2' marked B.O. bears S33°00'E 17.8 feet
(BLM S33°E 17.8 feet)
Pine snag 26" dia. bears record S30°E 2.6 feet
Pine stump 18" dia. bears S21°45'W 23.5 feet
(unknown origin BLM S22°W 23.4 feet)
D. Fir 10" dia. bears record S49°W 4.9 feet
Roothole with Pine stump alongside 14" dia. bears S68°24'W
41.0 feet (record S68°W 39.6 feet)
Roothole with Pine 14" dia. alongside bears N73°32'W 41.0 feet
(record N63°W 41.6 feet)
D. Fir 10" dia. bears N28°59'W 9.8 feet
(BLM N30°W 9.6 feet)
Pine snag 29" dia. bears N27°28'W 20.0 feet
(unknown origin BLM N28°W 19.8 feet)

1/4 corner $\frac{31}{10} \frac{2}{11}$: Set a 2" x 30" flanged GI Pipe with a
2-1/2" brass cap exposed 6" from which I mark the following
trees as required, taking measurements to the center of
the tree at the lower blaze in which I place a brass washer
LS 1679:

D. Fir 9" dia. bears S45°06'E 61.0 feet
P. Pine 8" dia. bears S26°52'W 40.1 feet

Section corner $\frac{31}{10} \frac{2}{11}$: Found standard BLM brass cap buried
8" in road dated 1967 (this monument is not of public record)
from which: