

Stump hole with down W. Larch 14" dia. bears N51°54'E 44.3 feet (record N52°E 44.2 feet)
 L. Pine 12" dia. bears N58°37'E 48.9 feet (BLM N61°E 48.8 feet)
 Fir 10" dia. bears S49°46'E 48.5 feet (BLM S46-1/2°E 47.5 feet)
 L. Pine 9" dia. bears S45°41'W 63.3 feet (BLM S46°W 62.7 feet)
 W. Larch stump bears S54°24'W 16.2 feet (record S52°W 15.8 feet)
 Fir 18" dia. bears N43°46'W 37.8 feet (BLM N42°W 15.8 feet)
 I mark a D. Fir 17" dia. bears N67°42'E 31.2 feet taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679.
 I mark a W. Fir 10" dia. bears S43°41'W 69.8 feet taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679.

E 1/16 corner 3: Set 2" x 30" flanged GI Pipe with 2-1/2" 10 brass cap exposed 5" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

W. Larch 14" dia. bears N80°50'W 31.5 feet
 W. Fir 8" dia. bears S32°44'E 31.3 feet

1/4 corner 3: Found standard BLM brass cap dated 1968 10 exposed 8" (this monument is not of public record) from which:

W. Larch 13" dia. bears N63°29'E 31.4 feet (BLM N63°E 31.7 feet)
 P. Pine snag 31" dia. bears S22°53'E 49.4 feet (record S43°E 50.2 feet)
 L. Pine 9" dia. bears S16°30'W 29.4 feet (BLM S17°W 29.7 feet)

Section corner 4/3: Set 2" x 30" flanged GI Pipe with 9/10 2-1/2" brass cap exposed 12" in a mound of stone from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

D. Fir 6" dia. bears N84°25'E 35.0 feet
 D. Fir 6" dia. bears S36°16'E 8.3 feet
 D. Fir 8" dia. bears S67°10'W 25.0 feet
 D. Fir 6" dia. bears N50°17'W 25.3 feet

1/4 corner 4/3: Found standard BLM brass cap dated 1968 exposed 2" in a mound of stone (this monument is not of public record) from which:

D. Fir 23" dia. bears S65°28'W 8.8 feet (record S68°W 8.6 feet)
 W. Fir 12" dia. bears N32°57'W 11.7 feet (record S58°E 11.2 feet)
 W. Larch 15" dia. bears S55°15'E 17.6 feet (record S58°E 17.8 feet)
 Spruce 8" dia. bears S23°08'E 18.0 feet (record S24°E 17.2 feet)

1/4 corner 4: Set 2" x 30" flanged GI Pipe with 2-1/2" 9 brass cap exposed 10" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679: