

(this monument is not of record) from which:

- Fir 14" dia. bears N66°35'E 25.5 feet
(BLM N68°E 25.4 feet)
- Fir 12" dia. bears S82°53'E 42.6 feet
(BLM S81°E 42.6 feet)
- Fir 16" dia. bears S6°27'W 48.8 feet
(BLM S7-1/2°W 48.8 feet)
- Fir 18" dia. bears N30°02'W 45.5 feet
(record N27°W 45.5 feet BLM N38°W 71.3 feet)

E 1/16 corner 2: Set a 2" x 30" flanged GI Pipe with
TT
a 2-1/2" brass cap exposed 7" in a mound of stone from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 11" dia. bears N79°38'E 15.6 feet
- D. Fir 13" dia. bears S39°25'W 32.5 feet

1/4 corner 2: Found a standard BLM Pipe and brass
TT
cap dated 1968 and exposed 10" in a mound of stone (this monument is not of record) from which:

- P. Pine 30" dia. bears S15°55'E 34.8 feet
(record S18°E 33.0 feet)
- Tamarack 12" dia. bears N21°02'W 29.2 feet
(BLM N23°W 29.0 feet)

Section corner 3|2: Found a standard BLM Pipe and
TOTT
brass cap dated 1967 and buried 8" in a Jeep road (this monument is not of record) from which:

- Dead and down Tamarack 14" dia. bears N51°54'E 44.3 feet
(record N52°E 44.2 feet)
- L. P. Pine snag 12" dia. bears N58°37'E 48.9 feet
(BLM Noble Fir 11" dia. N61°E 48.8 feet)
- Fir 10" dia. bears S49°46'E 48.5 feet
(BLM Black Pine 7" dia. S46-1/2°E 47.5 feet)
- L. P. Pine snag 9" dia. bears S45°41'W 63.3 feet
(BLM D. Fir 7-1/2" dia. S46°W 62.7 feet)
- Tamarack stump bears S54°24'W 16.2 feet
(record S52°W 15.2 feet)
- Fir 18" dia. bears N43°46'W 37.8 feet
(BLM Black Pine 14" dia. N42°W 38.3 feet)

from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 17" dia. bears N67°42'E 31.2 feet
- W. Fir 10" dia. bears S43°41'W 69.8 feet

N 1/16 corner 10|11: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 4" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 12" dia. bears N28°29'W 19.0 feet
- D. Fir 8" dia. bears N55°50'E 16.9 feet

1/4 corner 10|11: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 3" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 9" dia. bears N57°47'W 9.1 feet
- W. Fir 9" dia. bears N13°53'E 24.4 feet