

Section corner 10|11: Found a standard BLM Pipe and brass
15|14
cap dated 1968 set flush with the ground (this monument
is not of public record) from which:

- Spruce 13" dia. bears N42°40'E 23.8 feet
(BLM N45°E 23.1 feet)
- Spruce 18" dia. bears N34°31'E 21.4 feet
(record N46°E 21.1 feet)
- Spruce 10" dia. bears N30°49'W 43.1 feet
(BLM N29°W 42.9 feet)
- Fir snag 6" dia. bears S18°12'W 41.4 feet
(BLM S20°W 40.9 feet)
- Spruce 14" dia. bears S56°39'E 51.2 feet
(BLM S54°E 51.5 feet)

from which I mark the following trees as required,
taking measurements to the center of the tree at the
lower blaze in which I place a brass washer marked LS 1679:

Spruce 14" dia. bears S48°51'W 44.4 feet

1/4 corner 11: Set a 2" x 30" flanged GI Pipe with
14
a 2-1/2" brass cap exposed 10" in a mound of stones
from which I marked the following trees as required,
taking measurements to the center of the tree at the
lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 6" dia. bears N42°16'W 60.1 feet
- P. Pine 10" dia. bears S9°12'E 33.1 feet

Section corner 11|12: Found a standard BLM Pipe and
14|13
brass cap dated 1968 exposed 4" in a mound of stone
(this monument is not of record) from which:

- W. Fir 16" dia. bears N19°17'E 105.9 feet
(BLM N19-1/2°E 105.6 feet)
- P. Pine 40" dia. bears N27°36'E 55.1 feet
(record N28°E 55.4 feet)
- W. Fir 18" dia. bears S77°55'E 8.5 feet
(BLM S77°E 8.6 feet)
- Tamarack 11" dia. bears S52°42'W 20.4 feet
(BLM S53°W 20.5 feet)
- W. Fir 15" dia. bears N4°01'W 46.2 feet
(BLM N5°W 46.2 feet)

1/4 corner 12: Set a 2" x 30" flanged GI Pipe with
13
a 2-1/2" brass cap exposed 4" in a mound of stone,
from which I mark the following trees as required, taking
measurements to the center of the tree at the lower
blaze in which I place a brass washer marked LS 1679:

- D. Fir 6" dia. bears N46°31'W 69.2 feet
- W. Fir 7" dia. bears S33°05'W 41.7 feet

NE 1/16 corner Section 12: Set a 2" x 30" flanged GI
Pipe with a 2-1/2" brass cap exposed 4" in a mound
of stone, from which I mark the following trees as
required, taking measurements to the center of the
tree at the lower blaze in which I place a brass
washer marked LS 1679:

- P. Pine 8" dia. bears N37°39'E 38.2 feet
- P. Pine 9" dia. bears N79°48'W 4.2 feet

CN 1/16 corner Section 12: Set a 2" x 30" flange GI
Pipe with a 2-1/2" brass cap exposed 18" in a mound
of stone from which I mark the following trees as re-
quired, taking measurements to the center of the tree
at the lower blaze in which I place a brass washer
marked LS 1679:

- P. Pine 6" dia. bears N22°02'W 9.7 feet
- P. Pine 6" dia. bears S82°53'W 6.5 feet