

690

NW 1/16 corner Section 12: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 6" in a mound of stone, from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass wafer marked LS 1679:

D. Fir 12" dia. bears N25°37'W 32.0 feet  
P. Pine 9" dia. bears N53°22'E 50.4 feet

CW 1/16 corner Section 12: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 1" in a mound of stone, from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

W. Fir 8" dia. bears S44°14'E 18.9 feet  
W. Fir 7" dia. bears S62°12'W 17.0 feet

1/4 corner 11|12: Found a standard BLM Pipe and brass cap dated 1968, exposed 4" in a mound of stone (this monument is not of record) from which:

P. Pine snag 23" dia. bears N81°35'E 14.1 feet  
(record N88°E 14.5 feet; BLM N85°E 14.5 feet)  
P. Pine snag 30" dia. bears S36°59'W 23.9 feet  
(record S32°W 23.8 feet; BLM S35°W 23.8 feet)  
L. Pine 11" dia. bears N21°27'W 22.5 feet  
(BLM N23°W, 22.8 feet)

from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

W. Fir 8" dia. bears N73°11'E 7.9 feet  
W. Fir 7" dia. bears N11°05'W 7.9 feet

C 1/4 corner Section 11: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 6" in a mound of stone, from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

Spruce 7" dia. bears N00°09'E 8.0 feet  
D. Fir 14" dia. bears S58°22'E 61.6 feet

CW 1/16 corner Section 11: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 6" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

W. Fir 10" dia. bears N81°49'E 25.1 feet  
W. Fir 11" dia. bears S22°05'W 36.1 feet

NW 1/16 corner Section 11: Set a 2" x 30" flanged GI Pipe with a 2-1/2" brass cap exposed 2" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

W. Fir 10" dia. bears N50°22'W 4.9 feet  
W. Fir 8" dia. bears N53°19'E 19.8 feet

Bearing was based on a solar observation.

RECEIVED AND FILED

AUG 11 1981

OFFICE OF COUNTY SURVEYOR

*Robert O. Beget*  
Attest: *Carole Wright*  
*Co. clk.*

Surveyed By:

T. Flatebo & Associates, Inc.  
P.O. Box 900  
Jacksonville, OR 97530

Date:

Survey began - February 9, 1981  
Completed - April 29, 1981

REGISTERED PROFESSIONAL LAND SURVEYOR

*Kurt C. Weaver*  
OREGON  
JULY 14, 1978  
KURT C. WEAVER  
1679