

## SURVEY NARRATIVE TO COMPLY WITH O.R.S. 209.250

Survey For: The U. S. Forest Service  
Unatilla National Forest  
2517 S. W. Hailey Avenue  
Pendleton, Oregon 97801

Location: Located in Sections 3, 4, 9, 10, 15 and 16, Township 8 South, Range 32 East of the Willamette Meridian, Grant County, Oregon.

Purpose: To monument and mark the property boundaries of the National Forest lands located in Section 10 and to establish control for further surveying in the those sections.

Procedure: A search was made in the vicinities of all of those corners not previously recovered. During the initial investigation the quarter corner Sections 9 and 16 was recovered and remonumented. No evidence was recovered at the other corner positions.

A series of closed traverses was run through the found corners and proportion positions were determined for all missing corners. The proportion positions were then physically identified and further search for original evidence was made in those areas. From these areas, chained measurements were made to topographic calls for verification of relative position.

During this process the quarter corner of Sections 9 and 10 was recovered and monumented. Exhaustive search failed to yield any original evidence, however, at the North quarter corner of Section 9, the Northeast and the Southeast corners of Section 9, the South and East quarter corners of Section 10 or at the quarter corner of Sections 15 and 16.

The creek calls from the Northeast and the Southeast corners of Section 9 fit very well with the respective double proportionate positions for these corners.

The creek call near the quarter corner of Sections 4 and 9 fit good for distance, however, it lies on the opposite side the corner position than called for in the original notes.

The proportionate positions were monumented and the subdivision of Section 10 was performed. The heavy line in the Northeast quarter of Section 10 was marked as the property boundary of the National Forest lands with 6 foot steel fence posts with boundary signs attached.

The following corner monuments and accessories were recorded at the corners:

1/4 corner 4|3: Found standard BLM brass cap dated 1968 exposed 2" MOS (this monument is not of public record) from which:

- D. Fir 23" dia. bears S65°28'W 8.8 feet  
(record S68°W 8.6 feet)
- W. Fir 12" dia. bears N32°57'W 11.7 feet  
(record N30°W 11.2 feet)
- W. Larch 15" dia. bears S55°15'E 17.6 feet  
(record S58°E 17.8 feet)
- Spruce 8" dia. bears S23°08'E 18.0 feet  
(record S24°E 17.2 feet)