

691

Section corner $\frac{4}{9} \frac{3}{10}$: Set 2" x 30" Flanged GIP with
2-1/2" brass cap exposed 12" MOS from which I mark the
following trees as required, taking measurements to the
center of the tree at the lower blaze in which I place
a brass washer marked LS 1679:

D. Fir 6" dia. bears N84°25'E 35.0 feet
D. Fir 6" dia. bears S36°16'E 8.3 feet
D. Fir 8" dia. bears S67°10'W 25.0 feet
D. Fir 6" dia. bears N50°17'W 25.3 feet

1/4 corner $\frac{3}{10}$: Found standard BLM brass cap dated 1968
exposed 8" (this monument is not of public record) from
which:

W. Larch 13" dia. bears N63°29'E 31.4 feet
(BLM N63°E 31.7 feet)
P. Pine Snag 31" dia. bears S22°53'E 49.4 feet
(record S43°E 50.2 feet)
L. Pine 9" dia. bears S16°30'W 29.4 feet
(BLM S17°W 29.7 feet)

Section corner $\frac{10}{15} \frac{11}{14}$: Found standard BLM brass cap flush
with ground dated 1968 (this monument is not of public
record) from which:

Spruce 13" dia. N42°39'E 23.8 feet
(BLM N45°E 23.1 feet)
Spruce 18" dia. bears N34°31'E 21.4 feet
(record N46°E 21.1 feet)
Spruce 10" dia. bears N30°49'W 43.1 feet
(BLM N29°W 42.9 feet)
Fir snag 6" dia. bears S18°12'W 41.4 feet
(BLM S20°W 40.9 feet)
Spruce 14" dia. bears S56°39'E 51.2 feet
(BLM S54°E 51.5 feet)
I mark a Spruce 14" dia. bears S48°51'W 44.4 feet taking
measurements to the center of the tree at the lower
blaze in which I place a brass washer marked LS 1679.

1/4 corner $\frac{10}{15}$: Set 2" x 30" flanged GIP with 2-1/2"
brass cap exposed 11" from which I mark the following trees
as required, taking measurements to the center of the
tree at the lower blaze in which I place a brass washer
marked LS 1679:

L. Pine 8" dia. bears N62°00'W 15.4 feet
L. Pine 8" dia. bears S3°04'W 38.0 feet

Section corner $\frac{9}{16} \frac{10}{15}$: Set 2" x 30" flanged GIP with 2-1/2"
brass cap exposed 12" from which I mark the following
trees as required, taking measurements to the center of
the tree at the lower blaze in which I place a brass washer
marked LS 1679:

L. Pine 6" dia. bears N28°37'E 9.9 feet
L. Pine 8" dia. bears S56°33'E 6.8 feet
L. Pine 7" dia. bears S73°05'W 28.8 feet
L. Pine 6" dia. bears N87°50'W 11.4 feet
L. Pine 6" dia. bears N00°45'W 24.7 feet

Section corner $\frac{3}{10} \frac{2}{11}$: Found standard BLM brass cap buried
8" in road dated 1967 (this monument is not of public
record) from which:

Stump hole with down W. Larch 14" dia. bears N51°54'E
44.3 feet (record N52°E 44.2 feet)