

- L. Pine snag 12" dia. bears N58°37'E 48.9 feet
(BLM N61°E 48.8 feet)
- Fir 10" dia. bears S49°46'E 48.5 feet
(BLM S46-1/2°E 47.5 feet)
- L. Pine snag 9" dia. bears S45°41'W 63.3 feet
(BLM S46°W 62.7 feet)
- W. Larch stump bears S54°24'W 16.2 feet
(record S52°W 15.8 feet)
- Fir 18" dia. bears N43°46'W 37.8 feet
(BLM N42°W 15.8 feet)

I mark a D. Fir 17" dia. bears N67°42'E 31.2 feet, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679.
I mark a W. Fir 10" dia. bears S43°41'W 69.8 feet, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679.

North 1/16 10|11: Set 2" x 30" flanged GI Pipe with 2-1/2" brass cap exposed 4" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 12" dia. bears N29°28'W 19.0 feet
- D. Fir 8" dia. bears N55°50'E 16.9 feet

Center North 1/16 Section 10: Set 2" x 30" flanged GI Pipe with 2-1/2" brass cap exposed 8" mound of stone from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- D. Fir 13" dia. bears N24°43'W 16.3 feet
- W. Fir 9" dia. bears S23°33'W 33.1 feet

1/4 corner 10|11: Set 2" x 30" flanged GI Pipe with 2-1/2" brass cap exposed 30" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679:

- W. Fir 9" dia. bears N57°47'W 9.1 feet
- W. Fir 9" dia. bears N13°53'E 24.4 feet

1/4 corner 9|10: Set 2" x 30" flanged GI Pipe with 2-1/2" brass cap exposed 8" in a mound of stone from which:

- Fir stump 18" dia. bears N84°53'E 6.7 feet
(record N80°E 6.6 feet)
- W. Larch snag 10" dia. bears S84°47'W 12.6 feet
(record S80°W 12.5 feet)

I mark a Fir 9" dia. bears N17°09'E 12.0 feet taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679.
I mark a Fir 9" dia. bears N88°10'W 24.8 feet taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679.

1/4 corner $\frac{4}{9}$: Set 2" x 30" flanged GI Pipe with 2-1/2" brass cap exposed 10" from which I mark the following trees as required, taking measurements to the center of the tree at the lower blaze in which I place a brass washer marked LS 1679: