


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally set by Herman D. Gradon under Contract No. 499 dated March 11, 1884. The notes state that a marked basalt stone 24x12x4" was set 18" in the ground, from which:
 A 10" Fir bears S40°E 3 lks (2 feet) marked 1/4 S BT
 A 12" Tamarack bears N32° W 11 lks (7.3 feet) marked 1/4 S BT



No record of subsequent remonumentation found in County Records .

Description of corner evidence found:

After a diligent search of the area no evidence of the original corner was found. The corner was re-established by survey.

Description of monument and accessories established to perpetuate the original location of this corner

At the corner position a 2 inch by 30 inch iron pipe, with brass cap marked as shown, was set 18 inches in the ground and surrounded with a mound of stones to the cap .

Set a steel fence post North of corner and attached sign 54-4 .

Established 2 new BT's:

A 12" Fir bears S63 1/2° W 25.7 feet scribed 1/4 S 30 BT

A 9" Fir bears S51° E 34.7 feet scribed 1/4 S 29 BT

New BT's have a lower blaze scribed BT with brass washer stamped PLS 1106 nailed flush.

Attached signs 54-3 and 54-4 to all BT's and painted red ring around the trees above the upper blaze.

Used steel tape and magnetic compass with 19 1/2° east declination . Measured to center of Bts.

See map of survey


This corner set October 23, 1979

Witnesses: D. Kaufman, PLS
 D. Bartleson
 C. Kelly

REGISTERED
 PROFESSIONAL
 LAND SURVEYOR

William R. Wells

OREGON
 JULY 22, 1977
 WILLIAM R. WELLS
 1106



Office of County Surveyor County of Grant
 State of Oregon, I hereby certify that the within instrument was filed in this office
 for record on the 9 day of Jan 1980
Robert D. Buzza by _____
 (COUNTY OFFICIAL) (DEPUTY)