17 | 16 — N. 87° 46' 16" E. — 2617.72 — 16 | 15

20 | 21 — 21 | 22

2637.29

2752.81

N. 89° 42' 12" W. — 5308.69

2644.77 — C 1/4 COR. — N. 88° 18' 58" E. 1290.42 — S. 88° 15' 40" E. 1374.55 — 2663.92 — E. 1/4 COR. — N. 0° 33' 13" W. 10.00 — S. 88° 36' 45" E. 1323.13

N. 0° 27' 27" E. 169.00 — 162.71

S. 85° 30' 00" W. 320.00

N. 84° 59' 56" W. 92.39

N. 74° 00' 00" W. 400.00

N. 49° 25' 20" W. 397.80

N. 71° 00' 00" W. 740.00

N. 77° 59' 13" W. 475.90

N. 42° 17' 13" W. 360.00

N. 87° 33' 13" W. 335.50

N. 63° 20' 17" W. 140.02

S. 85° 52' 17" W. — 666.73 — N. 86° 46' 50" W. 320.51 — S. 85° 19' 14" W. 213.16

N. 0° 15' 32" E. 5274.57

2637.28

N. 0° 21' 20" W. 5391.53

2638.72

N. 0° 33' 13" W.

2640.10

1193.50

1526.60

1113.50

S. 0° 33' 13" E. 1520.00

343.10

N. 89° 45' 07" E.

STATE HIGHWAY

26

OREGON

Set offset Pin S 0° 33' 13" E 20.22

℄ Sta. 352+33 Set RR Spike

SURVEY NO. 160

BASIS OF BEARINGS
SURVEY NO. 160

20 | 21 — 2673.07 — 21 | 22

29 | 28 — N. 89° 40' 35" W. — 5346.14 — 28 | 27

LEGEND

- Fd. monuments of record.
- ◎ Fd. original G.L.O. corner, or acceptable evidence.
- ○ Set 5/8"x 30" iron pin, unless otherwise stated.

REGISTERED OREGON LAND SURVEYOR
JULY 10, 1964
DUANE I. GRIFFITH
644

RECEIVED AND FILED
JAN 6 1970
JOHN LIVEIRA, County Clerk
By _____ Deputy

BAGETT & GRIFFITH SURVEYING
John Day, Oregon

Map of Survey
Portion of Section 21
T 13 S, R 31 E, W.M.
Grant County, Oregon

| | | |
|---|---|---|
| Surveyed for | HINES LUMBER CO. | |
| Surveyed by | D.I.G. | Nov. 1969 |
| Scale: 1" = 200' | Drawn by D.I.G. | Nov. 1969 |

Map of Survey # 161