T13S R28E
Sec. 14

C1/4 cor.
Section 14

1305.14

CE 1/16 Cor.

T13S R28E
Sec. 13

C=E=1/64 Cor.

C=E=1/64 Cor.

C=E=1/64 Cor.

Scale 1"=100'

NARRATIVE

This survey was performed at the request of Dwin Dunkin. The purpose of this survey was to monument NW corner of Mr. Dunkin's property as described in Instrument No. 081798, deeds of Grant County, Oregon.

This survey was performed using static GPS receivers and Electronic Total Station. The GPS bearings were rotated clockwise 00°50'49" to true north. All bearings are relative to this local north meridian.

I used the brass cap monument set by Vernon Glaze at the E1/4 corner of Section 14 and the aluminum monument set by Ken Delano at the C1/4 corner of Section 14 to position the C-E-E1/64 corner shown hereon.

LEGEND

- Found 1½" iron pipe with attached 2" brass cap See Survey No. 7G.
- Found 2½" aluminum pipe with aluminum cap See Survey No. 1746.
- O Set 5/8"x30" iron pin with attached red plastic cap marked CORNERSTONE SURVEYING, INC.

x---x Fence Line

() Record bearing and distance.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
SEPT 19, 1995
JACK L. WATSON
2734

Renewal Date 6/30/2010

CORNERSTONE SURVEYING, Inc. 233 S. Canyon Blvd., John Day, Oregon 97845 (541) 575-1813

MAP OF SURVEY
SITUATED IN THE SE1/4 OF
SECTION 14, T13S, R28E, W.M.

GRANT COUNTY, OREGON

SURVEYED FOR: Dwin Dunkin

SURVEYED BY : Jack Watson
SURVEY COMPLETED: 12/15/2008

RECEIVED AND FILED

January 7, 2009

- GEFTON COUNTY SURVEYOR

Attest: