

CORNER NO.	MONUMENT	ACCESSORIES	CORNER NO.	MONUMENT	ACCESSORIES
①	Fd. 2 1/2" alum. cap in 1" G.I. pipe Set by Hambleton.	Fd. orig. BTS: 20" D. Fir brs S 63° E 42.4 ft.; 13" D. Fir (dead & down) brs S 60° W 34.3 ft. Fd. Hambleton's BTS: 7" D. Fir brs N 42° W 11.2 ft.; 16" D. Fir brs N 30° E 16.6 ft. Scribed BT: 9" Larch brs S 5° W 55.1 ft. scribed T9S R35E S28 BT.	②	Fd. 3" brass cap in 2 1/2" G.I. pipe-rock mound. Set by Wells.	Fd. orig. BTS: 11" P. Pine (down snag) brs N 73° 45' E 5.0 ft.; 16" W. Fir brs South 16.0 ft. Fd. Wells BT: 15" W. Fir brs S 54° E 48.0 ft.
②	Fd. 4" x 4" orig. post with visible scribings on 2 sides. Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BTS: 31" D. Fir brs N 65° W 5.9 ft.; 14" D. Fir brs S 60° W 5.3 ft. Scribed BT: 11" White Fir brs N 28° E 20.3 ft. scribed 1/4 S22 BT.	③	Fd. rock mound post hole 4 x 4 post some visible scribe rotted post in hole. Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BT: 15" D. Fir brs S 53° E 4.7 ft. scribed MS NO. 459 BT. Scribed BTS: 10" White Fir brs S 57° W 19.5 ft. scribed MS 459 BB SCE BT.
③	Fd. 2 1/2" alum. cap in 1" G.I. pipe Set by Hambleton.	Fd. orig. BTS: 24" Larch brs N 21° E 25.0 ft.; 22" Fir brs S 70° E 22.6 ft.; 25" Larch brs N 64° W 33.8 ft. Scribed BTS: 9" W. Fir brs S 12° E 50.7 ft. scribed T9S R35E S26 BT; 17" E. Spruce brs S 20° W 37.6 ft. scribed T9S R35E S27 BT.	④	Fd. 3" brass cap in 2 1/2" G.I. pipe Set by Wells.	Fd. orig. BTS: 9" L.P. Pine (dead down) brs N 17° 20' E 19.0 ft.; 10" L.P. Pine (dead) brs S 05° 45' W 19.0 ft. Fd. Wells BTS: 43" Larch brs S 16° E 112.6 ft.; 12" Larch brs N 26 1/2° W 16.1 ft.
④	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. BT by LS 645: 11" D. Fir brs N 39° W 26.4 ft. Scribed BT: 9" W. Fir brs S 85° W 13.6 ft. scribed MS 617 Q11 BT.	⑤	Fd. 3" brass cap in 2 1/2" G.I. pipe Set by Wells.	Fd. orig. BTS: 23" Larch brs N 10° 25' E 28.6 ft.; 21" Larch brs N 52° 45' E 10.0 ft. Scribed BT: 8" Eng. Spruce brs S 20° E 18.0 ft. scribed MS 459 BB3 BT.
⑤	Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Scribed BTS: 9" D. Fir brs S 37° E 30.4 ft. scribed "X" BT; 11" D. Fir brs S 65° W 16.6 ft. scribed "X" BT.	⑥	Fd. 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BTS: 27" Larch stump brs S 53° E 29.2 ft. Scribed BTS: 6" D. Fir brs N 25° E 49.2 ft. scribed MS 459 BB NCE BT; 7" Larch brs N 59° E 40.6 ft. scribed MS 459 BB NCE BT.
⑥	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe. Set by Hambleton.	Fd. orig. BTS: 22" P. Pine brs N 58° W 55.5 ft.; 25" D. Fir brs S 25° 20' W 82.5 ft.; 21" D. Fir brs S 87° 05' E 51.0 ft.; 21" P. Pine brs S 67° 50' E 76.4 ft.	⑦	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton.	Fd. orig. BT: 12" D. Fir (dead) brs S 25° 40' W 27.0 ft. Fd. Wells BTS: 13" D. Fir brs N 46° 30' E 9.2 ft. 14" D. Fir brs S 29 1/2° E 47.7 ft.
⑦	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton.	Fd. orig. BT: D. Fir (down snag) brs N 89° 50' W 32.8 ft.; Fd. Hambleton BTS: 10" P. Pine brs S 17° E 13.9 ft.; 10" W. Fir brs N 30° E 7.8 ft.	⑧	Fd. earth mound and remains of rotted post. Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BT: 20" Larch brs N 74 1/2° W 28.7 ft.; 16" Larch brs N 47° W 15.5 ft.
⑧	Fd. earth mound and remains of rotted post. Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BT: 20" Larch brs N 74 1/2° W 28.7 ft.; 16" Larch brs N 47° W 15.5 ft.	⑨	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Earth mound, set by Hambleton.	Fd. orig. BTS: 20" Larch brs S 29° 30' W 6.0 ft.; L.P. Pine (stump hole) brs S 89° 55' W 2.7 ft. Fd. Hambleton BT: 12" L.P. Pine (snag) brs N 76° E 20.5 ft. Scribed BTS: 9" W. Fir brs S 24° E 26.8 ft. Scribed MS 617 H02 BT; 10" W. Fir brs N 71° W 52.7 ft. scribed MS 617 H02 BT.
⑨	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Earth mound, set by Hambleton.	Fd. orig. BTS: 20" Larch brs S 29° 30' W 6.0 ft.; L.P. Pine (stump hole) brs S 89° 55' W 2.7 ft. Fd. Hambleton BT: 12" L.P. Pine (snag) brs N 76° E 20.5 ft. Scribed BTS: 9" W. Fir brs S 24° E 26.8 ft. Scribed MS 617 H02 BT; 10" W. Fir brs N 71° W 52.7 ft. scribed MS 617 H02 BT.	⑩	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. orig. BTS: 38" P. Pine brs South 23.0 ft.; D. Fir stump hole brs N 87° E 27.6 ft.; 25" W. Fir brs S 87° 05' E 51.0 ft.; 30" P. Pine brs S 67° 50' E 76.4 ft. Fd. Hambleton BT: 28" P. Pine brs N 51° W 6.0 ft.
⑩	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. orig. BTS: 38" P. Pine brs South 23.0 ft.; D. Fir stump hole brs N 87° E 27.6 ft.; 25" W. Fir brs S 87° 05' E 51.0 ft.; 30" P. Pine brs S 67° 50' E 76.4 ft. Fd. Hambleton BT: 28" P. Pine brs N 51° W 6.0 ft.	⑪	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton. Fd. remains of 4" x 4" sq. post with visible scribe.	Fd. orig. BTS: 17" D. Fir brs N 88° 55' E 28.7 ft.; 17" D. Fir brs S 47° 35' E 5.2 ft.
⑪	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton. Fd. remains of 4" x 4" sq. post with visible scribe.	Fd. orig. BTS: 17" D. Fir brs N 88° 55' E 28.7 ft.; 17" D. Fir brs S 47° 35' E 5.2 ft.	⑫	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. orig. BT: 16" W. Fir brs S 19° E 30.7 ft. Fd. Hambleton's BT: 17" D. Fir brs S 53° E 2.3 ft. Scribed BT: 17" D. Fir brs S 02° E 53.1 ft. scribed MS 709 QMS1 BT.
⑫	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. orig. BT: 16" W. Fir brs S 19° E 30.7 ft. Fd. Hambleton's BT: 17" D. Fir brs S 53° E 2.3 ft. Scribed BT: 17" D. Fir brs S 02° E 53.1 ft. scribed MS 709 QMS1 BT.	⑬	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. orig. BTS: 20" Larch brs N 47° 52' W 32.5 ft.; 14" Larch brs S 28° 23' W 37.0 ft. Scribed BT: 6" White Fir brs N 73° E 33.5 ft. scribed MS 709 QMS2.
⑬	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. orig. BTS: 20" Larch brs N 47° 52' W 32.5 ft.; 14" Larch brs S 28° 23' W 37.0 ft. Scribed BT: 6" White Fir brs N 73° E 33.5 ft. scribed MS 709 QMS2.	⑭	Fd. 2 1/2" brass cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. BTS set by Hambleton: 10" L.P. Pine snag brs N 65° E 26.2 ft.; 7" Larch brs S 20° E 10.9 ft. Scribed BT: 10" Eng. Spruce brs N 15° W 31.2 ft. Scribed MS 709 QMS3 BT.
⑭	Fd. 2 1/2" brass cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. BTS set by Hambleton: 10" L.P. Pine snag brs N 65° E 26.2 ft.; 7" Larch brs S 20° E 10.9 ft. Scribed BT: 10" Eng. Spruce brs N 15° W 31.2 ft. Scribed MS 709 QMS3 BT.	⑮	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. 8" L.P. Pine (down snag) brs N 22° 10' E 25.8 ft. Fd. BTS by Hambleton: 19" Larch brs N 34° W 14.9 ft.; 14" Larch brs S 16° W 21.4 ft.
⑮	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe Set by Hambleton LS 645.	Fd. 8" L.P. Pine (down snag) brs N 22° 10' E 25.8 ft. Fd. BTS by Hambleton: 19" Larch brs N 34° W 14.9 ft.; 14" Larch brs S 16° W 21.4 ft.	⑯	Fd. orig. rock mound. Set 2 1/2" brass cap in 2 1/2" x 30" pipe-rock mound.	Fd. orig. BTS: 12" Larch (windthrow) brs N 52° 45' E 16.7 ft.; 13" Larch brs N 06° 50' E 14.5 ft. Scribed BTS: 16" Larch brs N 64° W 39.8 ft. scribed MS 617 C NCE BT; 16" Larch brs S 12° E 28.8 ft. scribed MS 617 C NCE BT.
⑯	Fd. orig. rock mound. Set 2 1/2" brass cap in 2 1/2" x 30" pipe-rock mound.	Fd. orig. BTS: 12" Larch (windthrow) brs N 52° 45' E 16.7 ft.; 13" Larch brs N 06° 50' E 14.5 ft. Scribed BTS: 16" Larch brs N 64° W 39.8 ft. scribed MS 617 C NCE BT; 16" Larch brs S 12° E 28.8 ft. scribed MS 617 C NCE BT.	⑰	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe in old rock mound. Set by Hambleton.	Fd. orig. BT: 12" Larch brs S 69° 05' E 34.4 ft.; 18" Larch brs N 37° E 25.4 ft. Scribed BT: 10" Larch brs S 41° W 25.7 ft. scribed MS 617 Q42 BT.
⑰	Fd. 2 1/2" alum. cap in 1 1/2" G.I. pipe in old rock mound. Set by Hambleton.	Fd. orig. BT: 12" Larch brs S 69° 05' E 34.4 ft.; 18" Larch brs N 37° E 25.4 ft. Scribed BT: 10" Larch brs S 41° W 25.7 ft. scribed MS 617 Q42 BT.	⑱	Fd. rotted remains of corner post. Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BTS: 20" D. Fir stump brs N 17° 05' W 14.8 ft.; 10" L.P. Pine snag brs N 86° 25' E 22.3 ft. Scribed BTS: 11" D. Fir brs N 38° E 69.0 ft. scribed MS 617 Q4LWCE BT; 15" D. Fir brs S 60° W 35.9 ft. scribed MS 617 Q4LWCE BT.
⑱	Fd. rotted remains of corner post. Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. orig. BTS: 20" D. Fir stump brs N 17° 05' W 14.8 ft.; 10" L.P. Pine snag brs N 86° 25' E 22.3 ft. Scribed BTS: 11" D. Fir brs N 38° E 69.0 ft. scribed MS 617 Q4LWCE BT; 15" D. Fir brs S 60° W 35.9 ft. scribed MS 617 Q4LWCE BT.	⑳	Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. BTS: 33" W. Fir brs S 20° W 12.5 ft. (no record); 19" Larch stump brs S 70° E 25.8 ft. (no record). Scribed BTS: 9" D. Fir brs N 38° W 39.1 ft. scribed "X" BT; 8" W. Fir brs N 48° E 12.9 ft. scribed "X" BT.
㉑	Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	Fd. BTS: 33" W. Fir brs S 20° W 12.5 ft. (no record); 19" Larch stump brs S 70° E 25.8 ft. (no record). Scribed BTS: 9" D. Fir brs N 38° W 39.1 ft. scribed "X" BT; 8" W. Fir brs N 48° E 12.9 ft. scribed "X" BT.	㉒	Set 2 1/2" brass cap in 2 1/2" x 30" G.I. pipe-rock mound.	

NOTE: All new BTS are faced and marked per BLM manual and in addition have a brass washer marked LS 1305 nailed flush in lower blaze. All BTS are painted with 6" red band and tagged with appropriate signs. All caps are stamped as per BLM manual plus the Township, range, 1982 and PLS 1305. 6 ft. steel posts with appropriate signs were set 3 to 5 ft. from all corners as per contract. Field notes are in Books I and J contract. NO. 53-04M3-2-2789.

RECEIVED AND FILED

JAN 7 1983

OFFICE OF COUNTY SURVEYOR
Robert D. Smith
 Attest: *Thomas J. Lawrence*